

PART NO. OD & WALL LENGTH ST	LE MATERIAL	
CT-40 1/4" x .065 50 Feet Co	Copper, Annealed	MANIFOLD TUBING
CT-50 5/16" x .065 50 Feet Co	Copper, Annealed	
CT-60 3/8" x .065 50 Feet Co	Copper, Annealed	
		COIL

	PART NO.	DESCRIPTION	MATERIAL		
MANIFOLD TUBING	Fits PH-1 Pigtail Handle				
ADAPTOR BUSHINGS	BT-2M1	1/4" NPTF x 1/4" OD Tubing Recess	Brass		
	BT-2M2	1/4" NPTF x 5/16" OD Tubing Recess	Brass		
	BT-2M3	1/4" NPTF x 3/8" OD Tubing Recess	Brass		
	BT-2M1SS	1/4" NPTF x 1/4" OD Tubing Recess	St. Steel		
BT-2M2					

NESS230")	VALL THICK	* /0 /4" DIDE \4			PART NO.
		(3/4" PIPE W	("196" KNESS	WALL THICK	*(1/2" PIPE
		PIPE NIPPLES	THREADED I		
3/4" NPT	1-1/2"	WHF-3-9	1/2" NPT	1-1/2"	WHF-3-1
3/4" NPT	2"	WHF-3-10	1/2" NPT	2"	WHF-3-2
3/4" NPT	4"	WHF-3-11	1/2" NPT	4"	WHF-3-3
3/4" NPT	6"	WHF-3-21	1/2" NPT	6"	WHF-3-19
3/4" NPT	8-3/8"	WHF-3-13	1/2" NPT	8-1/2"	WHF-3-5
3/4" NPT	11-3/8"	WHF-3-16	1/2" NPT	11-1/2"	WHF-3-7
Sorvico	Acotylono 9	Suitable For	gon Sorvico	ad for Oxy	Cloan
Service	Acetylene S	Suitable For A	gen Service-	ed for Oxy	Clean
3/4" NPT 3/4" NPT	8 - 3/8" 11-3/8"	IF-3-13 IF-3-16	WH WH	1/2" NPT WH 1/2" NPT WH	8-1/2" 1/2" NPT WH

	PART NO.	LENGTH	SIZE	PART NO.	LENGT	I SIZE	
NOMINAL PIPE LENGTHS	CLEANED FOR OXYGEN						
BRASS ALLOY 360,	WHF-3-23	2"	1/2" Nom				
PRESSURES TO 3000 PSIG (20,700 kPa)	WHF-3-4	4"	1/2" Nom				
,	WHF-3-20	6"	1/2" Nom				
	WHF-3-6	8-1/2"	1/2" Nom				
	NOT CLEANED FOR OXYGEN						
SHORT PIPE LENGTH	WHF-3-120	6 Feet	1/2" Nom	WHF-3-122	6 Feet	3/4" Nom	
	WHF-3-17	12 Feet	1/2" Nom	WHF-3-18	12 Feet	3/4" Nom	
	Note: 12 Foot Lengths Must Ship Via Common Carrier						

PART NO.	REF A	REF B	REF F	ELBOWS			
WHF-4-8	1/2" NPT	1/2" NPT	1-1/4"	Figure 1	Pip	e Elbows, Fem	ale
WHF-4-11	3/4" NPT	3/4" NPT	1-3/8"	Figure 1	_	S TO 3000 PSIG (20	
WHF-4-15	1/2" NPT	.843"847"	1-1/4"	Figure 2	A	A	A
WHF-4-19	3/4" NPT	1.053"-1.057"	1-3/8"	Figure 2			
WHF-4-2	.843"847"	.843"847"	1-1/4"	Figure 3	F F	F F	F
.843"8	347" = 1/2" Pip	e Slip * 1.053"-1.05	F	— <u>B</u>	— <u>B</u>		
					FIGURE 1	FIGURE 2	FIGURE 3



			PART NO.	REF A	REF B	REF C & D	REF E	CROSSES	
Pipe Crosses, Female			WHF-4-9	1/2" NPT	1/2" NPT	1/2" NPT	2-1/2"	Figure 1	
PRESSURES TO 3000 PSIG (20,700 kPa)			WHF-4-12	3/4" NPT	3/4" NPT	3/4" NPT	2-3/4"	Figure 1	
E	E	E	WHF-4-16	.843"847"	.843"847"	1/2" NPT	2-1/2"	Figure 2	
			WHF-4-23	.843"847"	1/2" NPT	1/2" NPT	2-1/2"	Figure 3	
A B	A B	ABB	.843"847" = 1/2" Pipe Slip						
D	D	D							
FIGURE 1	FIGURE 2 (SLIP THROUGH)	FIGURE 3							

PART NO.	REF A	REF B	REF C	REF E	TEES	
WHF-4-7	1/2" NPT	1/2" NPT	1/2" NPT	2-1/2"	Figure 1	Pipe Tees, Female
WHF-4-10	3/4" NPT	3/4" NPT	3/4" NPT	2-3/4"	Figure 1	PRESSURES TO 3000 PSI (20,700 kPa)
WHF-4-14	.843"847"	.843"847"	1/2" NPT	2-1/2"	Figure 2	
WHF-4-18	1.053"-1.057"	1.053"-1.057"	3/4" NPT	2-3/4"	Figure 2	
WHF-4-13	1/2" NPT	1/2" NPT	.843"847"	2-1/2"	Figure 3	A B
WHF-4-21	.843"847"	1/2" NPT	1/2" NPT	2-3/4"	Figure 4	E   E
WHF-4-22	1.053"-1.057"	3/4" NPT	3/4" NPT	2-1/2"	Figure 4	FIGURE 1  C  FIGURE 2 (SLIP THROUGH)
WHF-4-1	1.053"-1.057"	1.053"-1.057"	1.053"-1.057"	2-3/4"	Figure 5	
.843"847" = 1/2" Pipe Slip* 1.053"-1.057" = 3/4" Pipe Slip						A B FIGURE 3 A B B E E

## **FEMALE NPT OUTLET ADAPTORS FOR** MANIFOLD PIPELINE, **BRASS & STAINLESS STEEL**

500 PSIG (3400 kPa) 3000 PSIG (20,700 kPa) 6000 PSIG (41,300 kPa)



PART NO.	GAS SERVICE	DESCRIPTION M	ATERIAL
	CGA	VALVE OUTLETS TO FEMALE PIPE THREADS	
		Commercial Acetylene, to 500 PSIG:	
15-1	CGA-300	RH Male .825"-14 NGO to 1/4" NPT Female	Brass
		Carbon Dioxide, to 3000 PSIG:	
CO-2-1	CGA-320	RH Male .825"-14 NGO, to 1/4" NPT Female	Brass
		Nitrous Oxide, to 3000 PSIG:	
1321-1	CGA-326	RH Male .825"-14 NGO to 1/4" NPT Female	Brass
		Air, to 3000 PSIG:	
1341-1	CGA-346	RH Male .825"-14 NGO to 1/4" NPT Female	Brass
	22121	Air, to 3000 PSIG:	
SS-1341-1	CGA-346	RH Male .825"-14 NGO to 1/4" NPT Female	St. Steel
0.47.1	604047	Air, to 5500 PSIG:	
347-1	CGA-347	RH Male .825"-14 NGO to 1/4" NPT Female	Brass
SS-347-1	CC 4 2 47	Air, from 3,001 to 5500 PSIG:	Cr Cr . l
33-34/-1	CGA-347	RH Male .825"-14 NGO to 1/4" NPT Female	St. Steel
800-1	CGA-350	Hydrogen, Natural Gas, to 3000 PSIG: LH Male .825"-14 NGO to 1/4" NPT Female	Brass
800-1	CGA-330	Medical Mixtures, to 3000 PSIG:	brass
500-1	CGA-500	RH Female .885"-14 NGO to 1/4" NPT Female	Brass
300-1	COA-300	POL Acetylene, Propane, to 500 PSIG:	Diass
16-1	CGA-510	LH Female .885"-14 NGO to 1/4" NPT Female	Brass
101	00/1010	POL Acetylene, Propane, to 500 PSIG:	Di doo
300-1	CGA-510	90° LH Female Nut .885"-14 NGO to 1/4" NPT Female	Brass
	00/1010	Oxygen, to 3000 PSIG:	2.000
415-1	CGA-540	RH Male .903"-14 NGO to 1/4" NPT Female	Brass
		Oxygen, to 3000 PSIG:	
SS-415-1	CGA-540	RH Male .903"-14 NGO to 1/4" NPT Female	St. Steel
		Butane, Propane Liquid, 3000 PSIG:	
414-1	CGA-555	LH Male .903"-14 NGO to 1/4" NPT Female	Brass
		Argon, Helium, Nitrogen to 3000 PSIG:	
416-1	CGA-580	RH Female .965"-14 NGO to 1/4" NPT Female	Brass
		Industrial Air, to 3000 PSIG:	
417-1	CGA-590	LH Female .965"-14 NGO to 1/4" NPT Female	Brass
		Refrigerant Gases, to 3000 PSIG:	
660-1	CGA-660	RH Male 1.030"-14 NGO to 1/4" NPT Female	Brass
		Refrigerant Gases, to 3000 PSIG:	
SS-660-1	CGA-660	RH Male 1.030"-14 NGO to 1/4" NPT Female	St. Steel
66 ( 17.1	604 (77	Argon, Helium, Nitrogen from 5,501to 7500 PSIG:	C. C. 1
SS-667-1	CGA-677	LH Male 1.030"-14 NGO to 1/4" NPT Female	St. Steel